

Product Information

Application Tape based on a one-sided embossed, transparent, dimensionally stable polyethylene film. Ideally suitable for transferring of all cast and calendered PVC CAD/CAM films.

Especially to be emphasised are the following properties:

- The film has a high tensile strength which ensures an exact positioning of all letters. The excellent flatness assists the easy application.
- The special acrylic adhesive is specially developed and has a constant high adhesive strength level. It can be removed without residues, even after a long period of application.
- Can be used for dry and wet application.
- Due to the embossed surface, the film unwinds easily. Static charging of the rolls is prevented.

Technical Data

| | |
|-------------------------|--------------------------------------------------------|
| Carrier: | transparent, embossed HDPE film |
| Adhesive: | Acrylic modified |
| Adhesion [N/cm]: | 2,00 +/- 20 % (Finat FTM1 after 20 min on PVC) |
| Thickness [mm]: | 0,13 +/- 10 % |

Standard Dimensions

1.220 mm x 100 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

POLI-TAPE Klebefolien GmbH

Zeppelinstraße 17
53424 Remagen – GERMANY

Phone: +49 (0) 2642 – 9836 0
Fax: +49 (0) 2642 – 9836 37

E-Mail: info@poli-tape.de
Internet: www.poli-tape.de

15/07/2020

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.