

POLI-CRAFT VINYL PERMANENT

Product Information

Monomeric PVC Film (gloss/matt, 90 µm) with clear, ecological compatible dispersion adhesive (semi-permanent), laminated on an Double-sided PE-coated silicone paper liner (120 g/m²).

A perfect glossy/matt face film in addition to high flexibility and conformability makes the product suitable also for non-smooth surfaces. Especially designed for vehicle lettering, decorating of windows, signs, etc. with excellent plotting, weeding and application characteristics.

Suitable for in- and outdoor mid-term applications.

Particularly suitable for application on flat and slightly curved surfaces. No adhesive residue after removal, if correctly applied.

POLI CRAFT VINYL is Prop 65 conform.

Shelf Life

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

Available Colours

5 gloss
21 matt

Standard Dimensions

30,5 mm x 183 cm / 24 in x 72 in

Technical Data

Carrier:	Monomeric PVC, highly stabilized, calendared
Thickness:	90 µm +/- 5%
Adhesive:	clear acrylic dispersion, semi-permanent
Adhesion:	> 4 N/cm
Adhesive application:	18 g/m ²
Liner:	Double-sided PE-coated silicone paper (120 g/m ²)
Application temperature:	+ 10 – + 40 °C
Temperature durability :	- 40 – +80 °C
Outdoor durability:	3 years

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.

POLI-CRAFT VINYL PERMANENT NEON

Product Information

Monomeric PVC Film (matt, 90 µm) with white, ecological compatible dispersion adhesive (semi-permanent), laminated on an Double-sided PE-coated silicone paper liner (120 g/m²).

A perfect matt face film in addition to high flexibility and conformability makes the product suitable also for non-smooth surfaces. Especially designed for vehicle lettering, decorating of windows, signs, etc. with excellent plotting, weeding and application characteristics.

Suitable for in- and outdoor mid-term applications.

Particularly suitable for application on flat and slightly curved surfaces. No adhesive residue after removal, if correctly applied.

POLI CRAFT VINYL is Prop 65 conform.

Shelf Life

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

Available Colours

4 matt

Standard Dimensions

30,5 mm x 183 cm / 24 in x 72 in

Technical Data

Carrier:	Monomeric PVC, highly stabilized, calendered
Thickness:	90 µm +/- 5 %
Adhesive:	white acrylic dispersion, semi-permanent
Adhesion:	> 4 N/cm
Adhesive application:	18 g/m ²
Liner:	Double-sided PE-coated silicone paper (120 g/m ²)
Application temperature:	+ 10 – + 40 °C
Temperature durability :	- 40 – +80 °C
Outdoor durability:	3 years

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.

POLI-CRAFT VINYL REMOVABLE

Product Information

Monomeric PVC Film (gloss/matt, 90 µm) with clear, ecological compatible dispersion adhesive (removable), laminated on an Double-sided PE-coated silicone paper liner (120 g/m²).

A perfect glossy/matt face film in addition to high flexibility and conformability makes the product suitable also for non-smooth surfaces. Especially designed for vehicle lettering, decorating of windows, signs, etc. with excellent plotting, weeding and application characteristics.

Suitable for in- and outdoor mid-term applications.

Particularly suitable for application on flat and slightly curved surfaces. No adhesive residue after removal, if correctly applied.

POLI CRAFT VINYL is Prop 65 conform.

Shelf Life

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

Available Colours

1 gloss
5 matt

Standard Dimensions

30,5 mm x 183 cm / 24 in x 72 in

Technical Data

Carrier:	Monomeric PVC, highly stabilized, calendared
Thickness:	90 µm +/- 5 %
Adhesive:	clear acrylic dispersion, removable
Adhesion:	> 1,8 N/cm
Adhesive application:	18 g/m ²
Liner:	Double-sided PE-coated silicone paper (120 g/m ²)
Application temperature:	+ 10 – + 40 °C
Temperature durability :	- 40 – +80 °C
Outdoor durability:	3 years

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.