POLI-TAPE®

TECHNICAL DATASHEET
ISSUE: 1
DATE: 02/06/2026

POLI-MOUNT 385

PRODUCT INFORMATION

POLI-MOUNT 385 is based on an UV-cross-linked, closed-cell polyethylene foam, laminated on both sides with a solvent acrylic adhesive. The adhesive offers an excellent resistance against ageing and temperature. The liner made by a siliconized polyethylene film (green) grants protection of the adhesive against all weather conditions.

Especially to be emphasised are the following properties:

- The high-grade solvent acrylic adhesive offers a high initial tack which guarantees an easy mounting under industrial conditions. Mounting of displays, product samples, plates and screens.
- The adhesive experiences a major increase of adhesion within the first 48 hours, and will reach a firm and solid final adhesion even under the influence of high temperatures and humid conditions.
- The permanent elastic and compressible PE-foam carrier is suitable for rough and uneven surfaces which contribute to an increase of the final adhesion strength.

TECHNICAL DATA

Carrier: PE-foam
Adhesive: Acrylic
Liner: PE-film, green
Adhesion [N/cm]: 4,20 +/- 10 %
Thickness [mm]: 1,00 +/- 5 %
Temperature resistance [°C]: -40 / +80

STANDARD DIMENSIONS

1.250 mm x 50 m

SAFETY DATA SHEET

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoff V and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 (REACH) and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

DISCLAIMER

The information on the physical and chemical properties and values contained in this document is based on tests we believe to be reliable; however, it does not constitute a guarantee. It is provided for informational purposes only, without warranty, and does not establish any guarantee. Buyers should independently verify the suitability of this material for their specific intended use prior to use. All technical data is subject to change. All POLI-TAPE products are sold in accordance with the terms and conditions of sale. For further information, please contact your POLI-TAPE sales representative. In the event of any ambiguity or discrepancy between the English version and foreign-language versions of this document, the English version shall prevail and take precedence.

POLI-TAPE Klebefolien GmbH
Zeppelinstraße 17
53424 Remagen - GERMANY
Phone: +49 2642 - 98 36 0
Fax: +49 2642 - 98 36 37
Email: info@poli-tape.de
Internet: www.poli-tape.de