

POLI-TACK 810

PRODUCT INFORMATION

POLI-TACK 810 is a thin and flexible, horizontal and vertical tear resistant, aluminized polyester film with an acrylic adhesive. POLI-TACK 810 is preferentially used for protection of screen print frames, isolation and decorative applications.

Especially to be emphasised are the following properties:

- Good resistance against ageing and chemicals.
- Excellent isolation against the impact of humidity and temperature.

TECHNICAL DATA

Carrier: PET-film, silver metallized

Adhesive: Acrylic

Adhesion [N/cm]: 3,20 +/- 10 %

Thickness [mm]: 0,06 +/- 5 %

Temperature resistance [°C]: -40 / +120

STANDARD DIMENSIONS

1.000 mm x 66 m

SAFETY DATA SHEET

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoff V and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 (REACH) and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

DISCLAIMER

The information on the physical and chemical properties and values contained in this document is based on tests we believe to be reliable; however, it does not constitute a guarantee. It is provided for informational purposes only, without warranty, and does not establish any guarantee. Buyers should independently verify the suitability of this material for their specific intended use prior to use. All technical data is subject to change. All POLI-TAPE products are sold in accordance with the terms and conditions of sale. For further information, please contact your POLI-TAPE sales representative. In the event of any ambiguity or discrepancy between the English version and foreign-language versions of this document, the English version shall prevail and take precedence.

POLI-TAPE Klebefolien GmbH
Zeppelinstraße 17
53424 Remagen - GERMANY
Phone: +49 2642 - 98 36 0
Fax: +49 2642 - 98 36 37
Email: info@poli-tape.de
Internet: www.poli-tape.de