

## POLI-TACK 870 UNIVERSAL

**PRODUKTBESCHREIBUNG** Transparent Polyester film coated with a cross-linked acrylic adhesive offering excellent temperature resistance, ageing and UV stability.

The adhesive can be removed without residue even after long periods of usage.

POLI-TACK 870 Universal transfer film is suitable for thermal transfer of heat-sealing substrates, i.e. for the transfer of Flex-film onto textiles.

- STANDARDABMESSUNGEN**
- 500 mm x 25 m
  - 500 mm x 40 m
  - 1.524 mm x 25 m\*
  - 1.524 mm x 40 m\*

\*Non-standard dimension. Converted after order entry. Extended delivery times may occur

**TECHNISCHE DATEN**

<b>Carrier:</b>	PET-film, transparent
<b>Adhesive:</b>	Acrylic
<b>Adhesion [N/cm]:</b>	0,50 +/- 10 %
<b>Thickness in [mm]:</b>	0,12 +/- 5 %
<b>Liner:</b>	Siliconised PP film, white

**SICHERHEITSDATENBLATT** When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities. Safety information in accordance with Regulation (EU) 2023/988 on general product safety from the European Parliament can be found at [www.poli-tape.de/safety](http://www.poli-tape.de/safety)

### DISCLAIMER

The information on the physical and chemical properties and values contained in this document is based on tests we believe to be reliable; however, it does not constitute a guarantee. It is provided for informational purposes only, without warranty, and does not establish any guarantee. Buyers should independently verify the suitability of this material for their specific intended use prior to use. All technical data is subject to change. All POLI-TAPE products are sold in accordance with the terms and conditions of sale. For further information, please contact your POLI-TAPE sales representative. In the event of any ambiguity or discrepancy between the English version and foreign-language versions of this document, the English version shall prevail and take precedence.

POLI-TAPE Klebefolien GmbH  
Zeppelinstraße 17  
53424 Remagen - GERMANY  
Phone: +49 2642 - 98 36 0  
Fax: +49 2642 - 98 36 37  
E-Mail: [info@poli-tape.de](mailto:info@poli-tape.de)  
Internet: [www.poli-tape.de](http://www.poli-tape.de)