

SUBLI-FLOCK 5901

PRODUCT INFORMATION

Heat-sealable Polyesterflock (white), with excellent results with dye-sublimation transfer-printing. The printing results are with bright and vivid colours due to high fibre density.

The liner on the hotmelt side allows motifs and logos to be cut by all current CAD/CAM plotters after printing. The Flock offers excellent weeding properties.

SUBLI-FLOCK 5901 is used for lettering on sport and leisure wear. Due to the dense flocking the printing results are bright and colourful. The Polyester-Flock is resistant to yellowing.

Nylon and textiles with a hydrophobic impregnation are not suitable for heat transfer.

We recommend evaluation on test material. This also applies to the sublimation inks and printers used.

Due to the various influences which occur from production and transfer of plotter letterings, consistency of the carrier materials and also washing and cleaning conditions, product liability can only cover the unprocessed material.

APPLICATION

- Print mirror-inverted on transfer paper with dyesublimation inks.
- Place transfer paper on flock and transfer the image by heat press at 185° C and medium pressure (2,0 bar) for 40 - 45 sec.
- Apply printed flock on textile by heat press

STANDARD DIMENSIONS

- 500 mm x 10 m
- 500 mm x 25 m

TECHNICAL DATA

Transfer Film: Polyester flock
Adhesive: Copolyester-hotmelt
Thickness [mm]: 0,64 +/- 10 %
Liner: Silicone-paper, white

TRANSFER CONDITIONS

Pressure: 2,5 - 3,0 bar [medium pressure]
Temperature/Time: 160°C, 15 sec.

WASH RESISTANCE

60 °C

Only colour detergent. Not suitable for dry-cleaning. Wash textiles inside out. Tumble dryable.

PRINTING:

Indirect using transfer paper.

SAFTY DATA SHEET

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore, it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities. Safety information in accordance with Regulation (EU) 2023/988 on on general product safety from the European Parliament can be found at www.poli-tape.de/safety.

DISCLAIMER

The information on the physical and chemical properties and values contained in this document is based on tests we believe to be reliable; however, it does not constitute a guarantee. It is provided for informational purposes only, without warranty, and does not establish any guarantee. Buyers should independently verify the suitability of this material for their specific intended use prior to use. All technical data is subject to change. All POLI-TAPE products are sold in accordance with the terms and conditions of sale. For further information, please contact your POLI-TAPE sales representative. In the event of any ambiguity or discrepancy between the English version and foreign-language versions of this document, the English version shall prevail and take precedence.

POLI-TAPE Klebefolien GmbH
Zeppelinstraße 17
53424 Remagen - GERMANY
Phone: +49 2642 - 98 36 0
Fax: +49 2642 - 98 36 37
E-Mail: info@poli-tape.de
Internet: www.poli-tape.de